

Tyre size	Pattern design	Load Index Speed Symbol	Additional marking	Fitting Single/ Dual	Speed symbol	Reference speed (km/h)	Maximum load capacity per axle (kg) at various cold inflation pressures (bar) 1)										
							6,50	6,75	7,00	7,25	7,50	7,75	8,00	8,25	8,50	8,75	9,00
265/70R19.5	NTR-827 HAKKA TRUCK 844	143/141J	-	Single	J	100	4280	4420	4570	4720	4860	5010	5160	5300	5450		
		143/141J	-	Dual	J	100	8090	8360	8640	8920	9190	9470	9750	10020	10300		
275/70R22.5	HAKKA TRUCK 844	148/145L	-	Single	L	120	4690	4850	5010	5170	5340	5500	5660	5820	5980	6140	6300
				Dual	L	120	8640	8940	9230	9530	9830	10120	10420	10710	11010	11310	11600
295/80R22.5	NTR-831 HKPL TRUCK E HKPL TRUCK F HAKKA TRUCK 861	152/148M	-	Single	M	130	5570	5760	5950	6150	6340	6530	6720	6910	7100		
		152/148M	-	Dual	M	130	9890	10230	10570	10910	11240	11580	11920	12260	12600		
		152/148M	-														
		152/148M	-														
315/70R22.5	NTR-831 HKPL TRUCK E HKPL TRUCK F HAKKA TRUCK 861	152/148M	154/150L	Single	M	130	5570	5760	5950	6150	6340	6530	6720	6910	7100		
		152/148M	154/150L	Dual	M	130	9890	10230	10570	10910	11240	11580	11920	12260	12600		
		152/148M	154/150L														
		152/148M	154/150L	Single	L	120	5590	5780	5970	6160	6350	6540	6730	6930	7120	7310	7500
315/80R22.5	NTR-831 HKPL TRUCK E HKPL TRUCK F HAKKA TRUCK 861	154/150M	156/150L	Single	M	130	6050	6260	6460	6670	6880	7090	7290	7500			
		154/150M	156/150L	Dual	M	130	10810	11180	11550	11920	12290	12660	13030	13400			
		154/150M	156/150L														
		154/150M	156/150L	Single	L	120	6280	6490	6710	6920	7140	7350	7570	7780	8000		
385/65R22.5	HKPL TRUCK F HAKKA TRUCK 861	158L	160K	Single	L	120	6670	6900	7130	7360	7590	7810	8040	8270	8500		
		158L	160K	Single	K	110	6700	6930	7160	7390	7620	7850	8080	8310	8540	8770	9000

1) The above inflation pressures are minimum values. On front axle use it is recommended to use the table values increased with 1,0 bar, but not exceed 9,0 bar pressures.