

Tyre size	Pattern design	Load Index Speed Symbol	Additional marking	Fitting Single/ Dual	Speed symbol	Reference speed (km/h)	Maximum load capacity per axle (kg) at various cold inflation pressures (bar) 1)																
							5,00	5,25	5,50	5,75	6,00	6,25	6,50	6,75	7,00	7,25	7,50	7,75	8,00	8,25	8,50	8,75	9,00
215/75R17.5	NTR 32	126/124M	-	S	M	130	2530	2640	2750	2860	2960	3070	3180	3290	3400								
				D	M	130	4760	4960	5170	5370	5580	5780	5990	6190	6400								
215/75R17.5	NTR 72	135/133J	-	S	M	100					3190	3300	3420	3540	3660	3770	3890	4010	4130	4240	4360		
				D	M	100					6020	6250	6470	6690	6910	7130	7350	7570	7800	8020	8240		
235/75R17.5	NTR 32	132/130M	-	S	M	130			2950	3060	3180	3300	3420	3530	3650	3770	3880	4000					
				D	M	130			5600	5820	6040	6270	6490	6710	6930	7150	7380	7600					
235/75R17.5	NTR 72	143/141J	-	S	M	100					3880	4020	4170	4310	4450	4590	4740	4880	5020	5160	5310	5450	
				D	M	100					7330	7600	7870	8140	8410	8680	8950	9220	9490	9760	10030	10300	
265/70R19.5	NTR 72	143/141J	-	S	J	100					3980	4130	4280	4420	4570	4720	4860	5010	5160	5300	5450		
	NTR 73	143/141J	-	D	J	100					7530	7810	8090	8360	8640	8920	9190	9470	9750	10020	10300		
275/70R22.5	NTR 32	148/145M	-	S	M	130					4370	4530	4690	4850	5010	5170	5340	5500	5660	5820	5980	6140	6300
				D	M	130					8050	8350	8640	8940	9230	9530	9830	10120	10420	10710	11010	11310	11600
295/80R22.5	NTR 32	152/148M	-	S	M	130					5190	5380	5570	5760	5950	6150	6340	6530	6720	6910	7100		
	NTR 45	152/148M	-	D	M	130					9210	9550	9890	10230	10570	10910	11240	11580	11920	12260	12600		
315/70R22.5	NTR 32	154/150L	152/148M	S	L	120					5200	5390	5590	5780	5970	6160	6350	6540	6730	6930	7120	7310	7500
		NTR 45	154/150L	152/148M	D	L	120					9300	9640	9980	10320	10660	11010	11350	11690	12030	12370	12720	13060
	NTR 32	NTR 45	154/150L	152/148M	S	M	130					5190	5380	5570	5760	5950	6150	6340	6530	6720	6910	7100	
					D	M	130					9210	9550	9890	10230	10570	10910	11240	11580	11920	12260	12600	
315/80R22.5	NTR 32	154/150M	156/150L	S	M	130					5640	5840	6050	6260	6460	6670	6880	7090	7290	7500			
				NTR 45	154/150M	156/150L	D	M	130					10070	10440	10810	11180	11550	11920	12290	12660	13030	13400
	NTR 32	NTR 45	154/150M	156/150L	S	L	120					5850	6060	6280	6490	6710	6920	7140	7350	7570	7780	8000	
					D	L	120					10070	10440	10810	11180	11550	11920	12290	12660	13030	13400		
315/80R22.5	NTR 68	156/150K	-	S	K	110					6010	6230	6450	6670	6890	7120	7340	7560	7780	8000			
				D	K	110					10070	10440	10810	11180	11550	11920	12290	12660	13030	13400			
385/55R22.5	NTR 72S	160K	158L	S	K	110					6250	6470	6700	6930	7160	7390	7620	7850	8080	8310	8540	8770	9000
				S	L	120					6210	6440	6670	6900	7130	7350	7580	7810	8040	8270	8500		
385/65R22.5	NTR 72S NTR 73S	158L	160K	S	L	120					6220	6440	6670	6900	7130	7360	7590	7810	8040	8270	8500		
				S	K	110					6240	6470	6700	6930	7160	7390	7620	7850	8080	8310	8540	8770	9000

1) The above inflation pressures are minimum values. On front axle use it is recommended to use the table values increased with 1,0 bar, but not exceed 9,0 bar pressures.